Profile

eLPie®
Choose to Craftspeople

THREE LAYER CO-EXTRUDED BLOWN FILM LINE

NEW ERA OF ELPIE BEGINS

ELPIE ENGINEERS PVT. LTD. with its head office in Rajkot, India is specialised in building high performance Plastic Extrusion machineries; Blown film line, Sheet Line & Thermoforming Machines, is founded in year 2010.

More than 30 years of experienced technocrat and founder of the company serves Elpie by tailoring plastic processing machineries including blown film lines and thermoforming machines as per customer requirements.

Elpie became an Award Winning Company in year 2013 for state of the art fully automatic and highest capacity, PP non woven spunbond single beam line designed for 3.2 meter fabric width, in initial stage from Elpie's inception.

Elpie is focused on PP Monolayer blown film line, LD/LLDPE/HDPE Multilayer blown film lines and machineries of EPS project, which includes EPS Sheet Extruder line, EPS Thermoformer and PS Extrusion Coating line.

Foil-eLP

eLPie®
Choose to Craftspeople

Foil-eLP covers monolayer & multilayer blown film lines that allow various configurations.From 8 ?m HDPE liner film to 5-layer barrier film with only a 1 ?m EVOH layer. Foil-eLP can produce a huge range of films for various packaging films like lamination grade films, liquid packaging films, ultra high barrier films, green house films, high dart FFS milk and water pouch film, meat and cereal packaging films, oil packaging films, shrink/stretch films, mulch films and soap packaging films.

All components of the Foil-eLP line have been fine-tuned to guarantee repeatable, excellent film quality at highest outputs. The extruders play a primary role and thanks to their universal screw for all types of resins; the line achieves exceptional melt quality at low melt temperatures.
Foil-eLP blown film lines also includes downward extrusion water quenched universal application to produce PP film to customer's specific requirements. For narrow width bags a twin die-head downward extrusion blown film line is also offered to produce narrow width PP bags for grocery and disposables packaging application. Entry-level machine Foil-eLP: LPB 40/750 line's brief specifications are listed below:

- **Screw Diameter =40 mm**
- **L/D Ratio =30**
- **Standard Die Diameter =100 & 200 mm**
- **Lay flat Width Range = 100-650 mm**
- **Film Thickness Range =20-60mircon**
- **Maximum output = 50 kg/hr**
- **Line Speed = 6.0 - 60mts./min.**
- **Total Installed Load = 32kw**
- **Line Dimension LxWxH = 5900 x 1900 x 4400 mm**

eLPie® ENGINEERS PVT. LTD.
Plot No. 2, Suvery No. 13/2/P1, N.H. - 27, Nr. Bharudi Toll Plaza,
Pipadiya (Village) - 360 311, Taluka : Gondal, Dis.: Rajkot, Gujarat, INDIA.
Mobile : +91 85111 19853 **Email :** info@elpie.in **Web :** www.elpie.in

NAVKAR : 9712 661144